

WHAT IS CLAIMED IS:

1. An image pickup apparatus comprising:  
first and second photoelectric conversion units  
each including a plurality of photoelectric conversion  
5 elements;

an image forming unit adapted to form images  
viewed from different points on the plurality of  
photoelectric conversion elements included in each of  
said first and second photoelectric conversion units;

10 a first holding unit adapted to hold signals from  
said first photoelectric conversion unit, said first  
holding unit including at least the same number of  
capacitors as the number of the plurality of  
photoelectric conversion elements included in said  
15 first photoelectric conversion unit;

a second holding unit adapted to hold signals from  
said second photoelectric conversion unit, said second  
holding unit including at least the same number of  
capacitors as the number of the plurality of  
20 photoelectric conversion elements included in said  
second photoelectric conversion unit; and

a first common output line to which signals are  
~~read out from the plurality of capacitors included in~~  
each of said first and second holding units.

25

2. An image pickup apparatus according to claim  
1, wherein said image forming unit includes microlenses

provided respectively in said photoelectric conversion units.

3. An image pickup apparatus according to claim  
5 1, further comprising:

third and fourth photoelectric conversion units each including a plurality of photoelectric conversion elements;

10 a second common output line to which signals are sequentially read out from said first and third photoelectric conversion units; and

a third common output line to which signals are sequentially read out from said second and fourth photoelectric conversion units;

15 wherein the plurality of capacitors included in said first holding unit hold the signals from said second common output line, and the plurality of capacitors included in said second holding unit hold the signals from said third common output line.

20

4. An image pickup apparatus according to claim  
1, wherein the photoelectric conversion unit includes  
an amplification unit for amplifying and outputting  
signals from the plurality of photoelectric conversion  
25 elements, said amplification unit being provided as a  
common amplification unit for the plurality of  
photoelectric conversion elements.

5. An image pickup apparatus according to claim 1, wherein each of said first and second holding units includes a capacity for holding at least the same number of noise signals as that of the plurality of photoelectric conversion elements; and

said image pickup apparatus further comprises a differential circuit adapted to subtract the noise signals from signals including photoelectric conversion signals generated by the photoelectric conversion.

6. An image pickup apparatus according to claim 1, further comprising a control circuit adapted to control to perform focus adjustment based on a plurality of signals outputted sequentially from said common output line.

7. An image pickup apparatus according to claim 2, further comprising microlenses provided respectively in said plurality of photoelectric conversion elements.

8. An image pickup apparatus comprising:  
first and second photoelectric conversion units each including a plurality of photoelectric conversion elements;

microlenses provided respectively in said first and second photoelectric conversion units, for focusing light onto the plurality of photoelectric conversion

elements included in each of said first and second photoelectric conversion units;

5 a first holding unit adapted to hold signals from said first photoelectric conversion unit, said first holding unit including at least the same number of capacitors as the number of the plurality of photoelectric conversion elements included in said first photoelectric conversion unit;

10 a second holding unit adapted to hold signals from said second photoelectric conversion unit, said second holding unit including at least the same number of capacitors as the number of the plurality of photoelectric conversion elements included in said second photoelectric conversion unit; and

15 a first common output line to which signals are read out from the plurality of capacitors included in each of said first and second holding units.

20 9. An image pickup apparatus according to claim 8, further comprising:

third and fourth photoelectric conversion units each including a plurality of photoelectric conversion elements;

25 microlenses provided respectively in said third and fourth photoelectric conversion units, for focusing light onto the plurality of photoelectric conversion elements included in each of said third and fourth

photoelectric conversion units;

a second common output line to which signals are sequentially read out from said first and third photoelectric conversion units;

5 a third common output line to which signals are sequentially read out from said second and fourth photoelectric conversion units;

10 wherein the plurality of capacitors included in said first holding unit hold the signals from said second common output line, and the plurality of capacitors included in said second holding unit hold the signals from said third common output line.

15 10. An image pickup apparatus according to claim 8, wherein said photoelectric conversion unit includes an amplification unit adapted to amplify and output signals from the plurality of photoelectric conversion elements, said amplification unit being provided as a common amplification unit for the plurality of  
20 photoelectric conversion elements.

11. An image pickup apparatus according to claim 8, wherein each of said first and second holding units includes a capacity for holding at least the same  
25 number of noise signals as that of the plurality of photoelectric conversion elements; and

said image pickup apparatus further comprises a

differential circuit adapted to subtract the noise signals from signals including photoelectric conversion signals generated by the photoelectric conversion.

5           12. An image pickup apparatus according to claim 8, further comprising a control circuit adapted to perform focus adjustment based on a plurality of signals outputted sequentially from said common output line.

10           13. An image pickup apparatus according to claim 8, further comprising microlenses provided respectively in the plurality of photoelectric conversion elements.

15           14. An image pickup apparatus comprising:  
an image pickup area including a plurality of photoelectric conversion elements; and

a plurality of microlenses for focusing light onto the plurality of photoelectric conversion elements;

20           wherein one microlens is provided for every photoelectric conversion element in a first image pickup region in said image pickup area, and one microlens is provided for every plurality of photoelectric conversion elements in a second image  
25           pickup region in said image pickup area.

15. An image pickup apparatus according to claim

- 43 -

comprising a drive c  
pickup region a mode  
the plurality of ph  
vided with a common  
and reading out signa  
tric conversion elem

1. The first part of the document is a list of references. The references are listed in a vertical column on the left side of the page. The references are as follows:

- 1. The first part of the document is a list of references. The references are listed in a vertical column on the left side of the page. The references are as follows: